



TECHNICAL SPECIFICATIONS

SPECIFICATION

Architecture	Video parts: Including Lens Image sensor USB interface controller
Color	Black
Interfaces	USB 2.0 with 2m cable
Lens	1/28" Fixed Focus 120 degree
Image Sensor	Full HD CMOS Sensor
Pitching Motion Angle	-30° ~ 30°
Horizontal Motion Angle	-150° ~ 150°
Video	1920x1080p
Image Transfer Rate	MJPEG @ 30fps YUV @ 5fps
F-Number	F2.0
Object Distance	30cm ~ 300cm
Power	USB Cable 2m Supply (5V/500mA)
Operating System	Windows 7/10 Mac OS X 8.1 or 10.7

Working Environment

Operating Temperature	0°C to 50°C
Dimension	104mm (L) x 139mm (W) x 124mm (H)
Weight	0.465g
Product Execution Standard	YD/T 993-1998 GB/T 9254-2008 GB 4843.1-2011

**SPEAKER PHONE SPECIFICATION**

Keypad	Audio Mute Volume up and Down
Audio Features	Digital Audio Processing 256ms echo Cancellation Dynamic noise reduction Full Duplex 360 degree pick-up range
Reverberation	< 0.5 Seconds
Wireless	2.4G Wireless
Power	Built-in lithium battery 7-10 Hours
Dimensions	155x148x37mm